clearswift

Ports and Protocols

Clearswift SECURE Web Gateway v4.x

Issue 1.7

18/04/2017



Copyright

Version 1.7, April, 2017

Published by Clearswift Ltd.

© 1995-2017 Clearswift Ltd.

All rights reserved.

The materials contained herein are the sole property of Clearswift Ltd unless otherwise stated. The property of Clearswift may not be reproduced or disseminated or transmitted in any form or by any means electronic, mechanical, photocopying, recording, or otherwise stored in any retrievable system or otherwise used in any manner whatsoever, in part or in whole, without the express permission of Clearswift Ltd.

Information in this document may contain references to fictional persons, companies, products and events for illustrative purposes. Any similarities to real persons, companies, products and events are coincidental and Clearswift shall not be liable for any loss suffered as a result of such similarities.

The Clearswift Logo and Clearswift product names are trademarks of Clearswift Ltd. All other trademarks are the property of their respective owners. Clearswift Ltd. (registered number 3367495) is registered in Britain with registered offices at 1310 Waterside, Arlington Business Park, Theale, Reading, Berkshire RG7 4SA, England. Users should ensure that they comply with all national legislation regarding the export, import, and use of cryptography.

Clearswift reserves the right to change any part of this document at any time.

Ports and Protocols



Contents

L	Cor	nnection Ports and Protocols	.4
	1.1	External Connections	.4
	1.2	Internal Connections	. 5
	1.3	HTTP/S Proxy support restrictions	. 7



1 Connection Ports and Protocols

The Clearswift SECURE Web Gateway requires connectivity to external services over a number of different ports and protocols.

Clients should be aware that these entries may be liable to change with limited notice as Clearswift extends its infrastructure to exceed demands.

Wherever possible, clients should configure their firewalls to utilize the hostname of the service and only use IP addresses if defining access by hostname is not possible.

1.1 External Connections

The following table summarizes the required connections from the Gateway to or from servers outside the organization.

Description	Protocol	Port	Direction	Hostname/URL	Current IP Address
FTP Over HTTP	TCP	20/21	Out		
DNS requests to Internet servers	UDP	53	Out/In		
Kaspersky AV updates	TCP	kav-update-8-2.clears kav-update-8-3.clears kav-update-8-4.clears kav-update-8-5.clears		kav-update-8-1.clearswift.net kav-update-8-2.clearswift.net kav-update-8-3.clearswift.net kav-update-8-4.clearswift.net kav-update-8-5.clearswift.net kav-update-8-6.clearswift.net	184.72.245.1 79.125.8.252 175.41.136.7 174.129.26.118 176.34.251.142 54.254.98.96
Sophos AV updates	ТСР	80	Out	sav-update-1.clearswift.net sav-update-2.clearswift.net sav-update-3.clearswift.net sav-update-4.clearswift.net sav-update-5.clearswift.net sav-update-6.clearswift.net	184.72.245.1 79.125.8.252 175.41.136.7 174.129.26.118 176.34.251.142 54.254.98.96
Kaspersky KSN lookup	TCP 443			Whilst this is on 443, the traffic is not standard HTTP/S, do not try and route through an SSL proxy	
Clearswift Update Server	TCP	80	Out	repo.clearswift.net rh.repo.clearswift.net	46.51.174.180 176.34.178.169
RSS Feed	ТСР	80	Out	www.clearswift.com	162.13.22.202
Appliance online help	TCP	80	Out	apphelpweb.clearswift.com	79.125.18.99
Service Availability List	TCP	80	Out	services1.clearswift.net services2.clearswift.net services3.clearswift.net	See https://ip- ranges.amazonaws.com/ip- ranges.json



Description	Protocol	Port	Direction	Hostname/URL	Current IP Address
URL Database Updates	ТСР	80	Out	url1.clearswift.net url2.clearswift.net url3.clearswift.net url4.clearswift.net	79.125.3.206 184.72.241.7 174.129.200.98 46.137.169.34
NTP server	UDP	123	Out/In	time.clearswift.net	Forms part of the NTP Pool project (http://www.pool.ntp.org)
Clearswift license key validation	ТСР	443	Out	applianceupdate.clearswift.com	86.188.240.24 213.106.99.208 46.236.38.70
General HTTPS web access	TCP	443	Out		
WCCPv2	GRE (47) TCP TCP	8444 9102	In In In		
PBR	TCP 8444 In TCP 9102 In				

1.2 Internal Connections

The following table summarizes the required connections from the Gateway to or from servers inside the organization.

Description	Protocol	Port	Direction	Comment
FTP/S Backup/Restore	TCP	20/21	Out	
SSH access to the Gateway Console	TCP	22	In	Disabled by default
SFTP Lexical data import	TCP	22	Out	To the server containing the lexical data
SFTP Backup & Restore	TCP	22	Out	To the backup server
SFTP Transaction Log Export	TCP	22	Out	To the log repository server
Outbound SMTP for alerts	TCP	25	Out	
DNS requests to internal servers	UDP	53	Out	
User Authentication using Kerberos	TCP	88	Out	
Ober Machemacadori doning Reliberos	UDP	88	Out	
NTP to internal server	UDP	123	Out/in	By default it is configured to connect to Clearswift NTP server



Description	Protocol	Port	Direction	Comment
User Authentication using NTLM	TCP UDP TCP TCP	135 137 139 445	Out Out Out Out	To directory servers
SNMP monitoring	UDP	161	In	From SNMP management servers
SNMP alerts	UDP	162	Out	
LDAP Directory access	TCP	389	Out	The port is configurable
Secure LDAP Directory access	TCP	636	Out	The port is configurable
HTTPS access to the Gateway's Web Interface	TCP	443	In	
HTTPS Lexical data import	TCP	443	Out	To the server containing the lexical data
SYSLOG export	TCP	514	Out	To the central SYSLOG server
FTPS Lexical data import	TCP	990/21	Out	To the server containing the lexical data
FTPS Backup & Restore	TCP	990/21	Out	To the backup server
FTPS Transaction Log Export	TCP	990/21	Out	To the log repository server
SCOM Monitoring	TCP	1270	In	From the SCOM server
LDAP connection to an active directory global catalogue	TCP TCP	3268 3269	Out Out	
Master/Slave HTTPS configuration	TCP TCP TCP	8071 8070 8090	In (Master) In (Slave) In (Slave)	Communications are always between Master and Slaves. So "In" for Master means "Out" from Slaves to Master
Distribution of information to peer appliances	UDP	9000	In/Out	This port is configurable through the Web UI



1.3 HTTP/S Proxy support restrictions

Customers using HTTP/S proxies will suffer from 2 issues

- 1. If customers are using Kaspersky AV with Cloud Lookup enabled will not be able to decrypt the 443 connection due to it being a proprietary protocol
- 2. Customers performing license validation can either bypass content inspection on the proxy or deploy a client certificate to enable the SSL content to processed and validate the license key correctly.